

DS-3E0310HP-E
8 Port Fast Ethernet Unmanaged PoE Switch



▪ Specification

Model		DS-3E0310HP-E
General	Shell	
	Net Weight	
	Gross Weight	
	Dimensions (W × H × D)	227.6 mm × 271.8 mm × 100.13 mm (9.0" × 10.7" × 3.9")
	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating Humidity	
	Relative Humidity	
	Power Supply	
	Max. Power Consumption	120 W
	Power Consumption in Idle	10 W
	Installation Mode	
	Surge Protection	
Network Parameters	Ports	
	MAC Address Table	
	Switching Capacity	5.60 Gbps
	Packet Forwarding Rate	4.17 Mpps
	Internal Cache	
PoE Power Supply	PoE Standard	
	PoE Power Pin	
	Max. Port Power	Ports 2 to 8: 30 W
	PoE Port	Hi-PoE: Port 1
	PoE Power Budget	
Dialing Function	Long Range	
Software Function	VIP Port	Ports 1 to 8: data on VIP ports is preferentially forwarded when bandwidth resources are insufficient.
Approval	EMC	
	Safety	UL (UL 60950-1), CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	

▪ Available Model

DS-3E0310HP-E

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global

Hikvision
Corporate Channel

hikvisionhq