

DS-3E0526P-E

24 Port Gigabit Unmanaged PoE Switch



▪ Specification

Model		DS-3E0526P-E
General	Shell	
	Net Weight	
	Gross Weight	
	Dimensions (W × H × D)	110.0 mm × 110.0 mm × 220.0 mm (4.33" × 4.33" × 8.67")
	Operating Temperature	−10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	−40 °C to 85 °C (−40 °F to 185 °F)
	Operating Humidity	
	Relative Humidity	
	Power Supply	
	Max. Power Consumption	400 W
	Power Consumption in Idle	30 W
	Installation Mode	
	Surge Protection	
Network Parameters	Ports	
	MAC Address Table	
	Switching Capacity	52 Gbps
	Packet Forwarding Rate	38.69 Mpps
	Internal Cache	
PoE Power Supply	PoE Standard	
	PoE Power Pin	
	PoE Port	
	Max. Port Power	30 W
	PoE Power Budget	370 W
Approval	EMC	
	Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
	Chemistry	

▪ Accessory

▪ Optional

HK-SFP-1.25G-20-1550 SFP Module	HK-SFP-1.25G-20-1310 SFP Module	HK-SFP-1.25G-1310-DF- MM SFP Module	HK-SFP-1.25G-20-1310- DF SFP Module
			

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq