

Tenda



All for better networking.

W15E

AC1200 Wireless Hotspot Router

www.tendacn.com



Link
More

W15E

AC1200 Wireless Hotspot Router

What it does

W15E is designed to provide wireless network for small office, internet café, large house etc premise. It is compliant with 802.11a/n/ac standard and delivers wireless rate up to 1200Mbps. Features with external power amplifier and 4 high gain antenna, it provide superior wireless coverage and high quality wifi connection experience for mobile user. Adopt of 11ac dual band,airtime fairness,5G bandsteering etc wireless optimization technology to improve wireless user capacity and ensure high qualified Wi-Fi connection.

Main Features

2.4GHz 11n 300Mbps


5GHz 11ac 867Mbps

Multi WAN Load Balance

Captive Portal


Smart bandwidth control

PPTP/L2TP/IPSec Server



High Density User Access

Adopt of 11ac dual band 1167Mbps rate,airtime fairness,5G bandsteering etc wireless optimization technology to improve wireless user capacity and ensure high qualified Wi-Fi connection.



Smart Bandwidth Control

W15E features with smart bandwidth management. It will adjust each user's download and upload bandwidth automatically according to all users bandwidth usage to avoid bandwidth insufficient.




Multi WAN Load Balance

W15E supports 3 WAN ports. It can realize bandwidth averaging between two WAN ports base IP Group. Also it reserve the possibility of bandwidth expansion in the future.



Captive Portal

W15E integrates with captive portal service. A landing page will pop-up when mobile device connect to wifi network. Once username and password is provided, the user will be able to access Internet.



PPTP/L2TP/IPSec Server

W15E supports multiple VPN protocols including IPsec, PPTP and L2TP in Client/Server mode. It is easily to setup a secure data link between branch and headquarter through LAN-to-LAN/Client-to-LAN mode.

Specifications

Hardware Specifications

Dimension	225*135*30(mm)(LxWxH)
Frequency	2.4GHz\5GHz
Wireless Speed	300+867Mbps
RAM	128MB
FLASH	8MB
Max Power Consumption	9W
Interfaces	4*FE(1~3 WAN/ 1~3 LAN)
Power	9V 1A

Hardware Specifications

Max user capacity	50
Max Wifi user capacity	30
Internet Connection Type	PPPoE/DHCP/Static IP/Russian L2TP/India
Authrization Service	Captive Portal
Captive Portal	50 Portal Accounts
	Customize E-bulletin
Bandwidth Control	Smart Bandwith Control
	Manual Definition
Internet Access Control	IP/mac/URL Filter
VPN Protocal	PPTP、L2TP、IPSEC
Port Forwarding	Port Forwarding
	DMZ
Security Setting	DDoS Protection
	ARP Attack Protection
DDNS	Support
UPNP	Support
Firmware Upgrade	Local
	online Upgrade
System Tool	Schedule Reboot
	Restore or Backup Configuration
Network Status View	Network structure topology
	Traffic Statistics

www.tendacn.com

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int' IE-City,
#1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail: support@tenda.cn

Tel: 0755-2765 7098

Fax: 0755-2765 7178

PC: 518055